

PT-8850 Feature

Special Features :

- Support high performance Intel® CPU
- Two-sided operation
- 15" touch screen
- Adjustable monitor
- Power USB

Optional :

- Solid State Drive
- Dual display (with or without touch)
- Additional 2nd hard drive
- Fingerprint reader
- Magnetic card reader
- KB-32 keypad
- RFID reader
- Rear VFD Customer display
- Capacitive touch screen



MSR



Keypad



I-Button



Biometric



PT-8850

**High Performance
POS Terminal**

PT-8850 Series

The PT-8850 series is a top-of-the-line POS terminal system with an impressive technological configuration. The PT-8850 series has variety choice of high performance CPU-Intel Core™ Duo, Intel Pentium Dual-core or Intel Celeron. Whichever configuration you choose, outstanding processing power is guaranteed.

The PT-8850 series is also available with an additional attached customer facing 15" touch LCD display offering unlimited digital signage solutions. This means customers can follow the checkout transaction while providing visual content to help drive up-selling or education of upcoming sales and events. The PT-8850 series has limitless configurations when considering customer marketing ideas. The space saving design and easy set up make the PT-8850 the system of choice for the discerning environment.



0-60 degrees tilt angle



15" Dual Display



Rear Customer Display



IC Card Reader, USB 2.0 Ports,
Compact Flash Reader



Support Multi Reader



Spill proof design

| Item | PT-8850 |
|---|---|
| CPU Type | Intel Core™ 2 Duo E6400 2.13GHz or Intel Pentium Dual-core E2160 1.80GHz or Intel Celeron 440 2.0GHz |
| Memory | 1GB (up to 4 GB) |
| LCD | 15" Active TFT color LCD, resolution 1024 x 768 |
| Touch | 5-wire Resistive touch (RS-232 interface) |
| Storage | 3.5" type SATA HDD (support 2 HDD) |
| Ethernet | 10/100M/1000 Mbps |
| I/O Interface | 6 * COM ports (COM1~4 at back I/O, COM5~6 on M/B) (COM1~4 provides DC +5V/12V with BIOS setting) 1 * DB-15 VGA port 1 * DB-25 for LPT port 1 * RJ11 port for 2 cash drawer(+24V) 1 * PS2 Keyboard port 1 * PS2 Mouse port 1 * RJ-45 LAN port with activity and link LEDs 2 * Audio ports (1 * Line-out , 1 * MIC-in) 4 * USB 2.0 ports (2*powered USB (DC+12V and DC+24V) on rear I/O panel, 2*USB on front) |
| Optional Peripherals | 3 tracks magnetic reader Customer display module (2 x 20 VFD) 802.11 b/g/n Mini PCI-e Module support WiFi function Biometric Reader or Smart Card Reader or I-Button or RFID reader KB-32 32-keys keypad 2 nd monitor(Dual screen) uSSD (8850/8950) |
| Expansion Options | 1 * Mini PCI-e |
| Operation System | Windows Vista, XP, XP embedded, Linux (Fedora) , WEPOS, POSReady |
| Dimensions | 344mm (W) x287mm (D) x 375mm (H) |
| Power Supply | AC100~240V 220watt |
| Operating Temperature | 0°C ~ +40°C |
| Storage Temperature | -20°C ~ +60°C |
| Operating & Storage Humidity | 10%~80% |
| Certification | CE/FCC Class A, UL, cUL, CB, VCCI, BSMI |



Partner Tech Corporation

Taiwan TEL:+886-2-29188500

FAX:+886-2-29153405

E-mail:sales@partner.com.tw

USA TEL:+1-949-598-1888

FAX:+1-949-598-0088

E-mail:sales@partnertechcorp.com

Europe TEL:+49 (0)40 450 635-0

FAX:+49 (0)40 450 635-130

E-mail:info@partner-tech.eu

UK TEL:+44 (0)1928 579 707

FAX:+44 (0)1928 571 308

E-mail:sales@partnertech-uk.com

China TEL:+86-21-67696667

FAX:+86-21-67696699

E-mail:sales@partnertech.com.cn

Korea TEL:+82-2-2090-7559

FAX:+82-2-2090-7558

E-mail:adams_c@partnertech.com.cn

