

# SE100 All-in-One LCD Touch POS Terminal

- Flexible features designed to exceed your POS requirements
- Integrated customer display, magnetic stripe reader (MSR) and smart card reader



Rear display



Smart Card



MSR



## Announcing the New SEIOO point of sale solution.

- Small footprint
- Integrated customer display, magnetic card reader, and smart card reader
- Ultra fast integrated 10/100/1000M network interface
- Open OS architecture handles a broad range of software applications
- Multiple accessory designs options to fit your needs



### Specifications

<b>Processor</b>	Intel Celeron-M 1GHz (0K L2 cache) or Celeron-M 1.5 GHz CPU (512K L2 cache)
<b>System Memory</b>	256MB DDR up to 2GB, 2 memory slots
<b>Display</b>	15" Active TFT color LCD
<b>Resolution</b>	1024x768
<b>LCD Brightness</b>	250 nits (w/o touch)
<b>Viewing Angle</b>	0° to 60° tilt
<b>Touch Screen</b>	5-wire resistive or optional capacitive
<b>Network</b>	10/100/1000M on board Ethernet controller
<b>Storage</b>	1x3.5" hard drive
<b>Expansion Options</b>	<ul style="list-style-type: none"> <li>• Compact flash card socket, IDE interface</li> <li>• 1 mini-PCI</li> </ul>
<b>Power Supply</b>	100~240vAC, DC+19V, 90W power adaptor
<b>IO Ports</b>	<ul style="list-style-type: none"> <li>• 4* RS232 ports, com 3 &amp; 4 provide +5/12V through jumper free BIOS setting</li> <li>• 1* parallel port</li> <li>• 1* PS/2 KB</li> <li>• 1* PS/2 mouse</li> <li>• 2* USB 2.0 ports in front</li> <li>• 2* USB 2.0 ports in rear</li> <li>• 1* DB-15 VGA port</li> <li>• 1* RS45 LAN port</li> <li>• 1* RJ-11 24Vdc cash drawer port</li> <li>• 2* Audio ports (1 line-out, 1 MIC-in)</li> </ul>
<b>Operation System</b>	Windows 2000/XP Pro/XPE/CE.Net/WEPOS/Linux
<b>Peripherals</b>	<ul style="list-style-type: none"> <li>• Dual or three track magnetic card reader</li> <li>• Smart Card Reader</li> <li>• 2x20 VFD customer display</li> </ul>
<b>Temperature</b>	<ul style="list-style-type: none"> <li>• Operating Temperature: 0~40° C</li> <li>• Storage Temperature: -20~60° C</li> </ul>
<b>Humidity</b>	<ul style="list-style-type: none"> <li>• Operating Humidity: -20%~85%</li> <li>• Storage Humidity: -5%~85%</li> </ul>
<b>Dimension</b>	<ul style="list-style-type: none"> <li>• Physical: 344(W)x287.3(D)x352(H)mm</li> <li>• Package: 490(W)x400(D)x441mm(H)</li> </ul>
<b>Weight</b>	10kg
<b>Certification</b>	CE/FCC Class A, UL, cUL, VCCI, BSMI

\*Specification may subject to change without prior notice